

MAGLIFT - Tekniska specifikationer



Description

MAGLIFT har designats speciellt för gaffeltruckar inom industri- och logistikverksamhet. Det robusta däck erbjuder hög lastkapacitet och enastående komfort. MAGLIFT har utmärkt motståndskraft mot skärande underlag och punkteringar, vilket ger lång livslängd. Den förstärkta strukturen motverkar risken för slirning, samtidigt som den speciella vulstformen underlättar påtagning av däck.

UM

US Standard

Construction

◆ SOLID

Machinery

Industri: Gaffeltruck

Version

LIP - NON MARKING

Type

Tyre Size

7.50 - 15

Dimensions US Standard

Usa code	94054725
Section Width (inch)	7.6
Overall Diameter (inch)	29.8
Rim Rec	6.0 - 15

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	8600
15 STEER WHEEL	6615

Printed on 4/20/2024 11:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..