

MINEFORCE - Tekniska specifikationer



Description

MINEFORCE är ett bias-lager-däck speciellt designat för lastbilar i gruvdrift och stenbrott. MINEFORCE högpresterande lastbilsdäck är BKT:s innovativa svar på steniga, slitande och tuffa gruvmiljöer. Det har ett unikt däkmönster med speciellt utvecklade slitbanesammansättningar för hårda, steniga och tuffa gruvförhållanden. Dess stora kontaktyta med hårda kanter ger jämnt mönsterslitage och en längre livscykel.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Stel dumper

Version	CUT RESISTANT
Type	TL
Tyre Size	24.00 - 35

Dimensions International Standard

Ply Rating	48
TKPH	370
Overall Width (mm)	655
Overall Diameter (mm)	2190
Static Loaded Radius (mm)	1003
Rolling Circumference (mm)	6482
Rim Rec	17.00/3.5
TRA Code	E4
Tread Depth	68

Load capacity (Kg)

km/h / bar	6.50	8.50
50	18500	-
10	-	31500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/9/2025 4:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..