

MP 567 - Tekniska specifikationer



Description

MP 567 är ett industridäck för lantbruket som lämpar sig för åker- och vägtransporter samt verksamheter inom kommun/underhåll. Det här är det perfekta däck för teleskoplastare och arbetsfordon. MP 567 ger god dragförmåga i alla väderförhållanden och erbjuder utmärkta självrensande egenskaper. Däck är en garanti för en bekväm körupplevelse och har lång livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Teleskoplastare

Industri: Teleskoplastare • Universalfordon

Version	IMPLEMENT
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	123 A8

Dimensions International Standard

Ply Rating	10
TKPH	1
Section Width (mm)	258
Overall Diameter (mm)	774
Static Loaded Radius (mm)	365
Rolling Circumference (mm)	2401
Rim Rec	9.0
ECE	E11-106R-003526

Load capacity (Kg)

km/h / bar	3.90
40 FR	1550
40 DW	1090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 21:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..