

## MP 567 - Tekniska specifikationer



### Description

MP 567 är ett industridäck för lantbruket som lämpar sig för åker- och vägtransporter samt verksamheter inom kommun/underhåll. Det här är det perfekta däck för teleskoplastare och arbetsfordon. MP 567 ger god dragförmåga i alla väderförhållanden och erbjuder utmärkta självrensande egenskaper. Däcket är en garanti för en bekväm körupplevelse och har lång livslängd.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Teleskoplastare  
Industri: Teleskoplastare • Universalfordon

Version	STANDARD
Type	TL
Tyre Size	10.5 - 20

## Dimensions US Standard

Usa code	94038091
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	37.6
Static Loaded Radius (inch)	17.5
Rolling Circumference (inch)	113.4
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022630

## Load capacity (lbs)

mph / psi	54
55	3970
25	4560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 8:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..