

MP 570 - Tekniska specifikationer



Description

MP 570 är ett industridäck för lantbruket som lämpar sig för grävmaskiner och grävlastare. Däcket har god dragförmåga och hållbarhet och erbjuder utmärkta självrensande egenskaper under alla driftförhållanden.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Grävlastare

Industri: Grävlastare • Grävmaskin • Universalfordon

Version	STANDARD
Type	TL
Tyre Size	14.5 - 20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	360
Overall Diameter (mm)	1116
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3325
Rim Rec	11
Rim Alt	12 SDC
ECE	E11-106R-005342

Load capacity (Kg)

km/h / bar	3.00
65	2430
50	2500

Printed on 4/19/2024 5:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..