

## MP 600 - Tekniska specifikationer



### Description

MP 600 är ett industridäck för lantbruket som lämpar sig för kommun-/underhållsverksamhet med teleskoplastare och arbetsfordon och ger en bekväm körupplevelse. Däcket har god dragförmåga och utmärkta självrensande egenskaper samt extra lång livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Teleskoplastare  
Industri: Teleskoplastare • Universalfordon

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	308
<b>Overall Diameter (mm)</b>	990
<b>Static Loaded Radius (mm)</b>	450
<b>Rolling Circumference (mm)</b>	2950
<b>Rim Rec</b>	11
<b>Rim Alt</b>	12 SDC

## Load capacity (Kg)

	km/h / bar	3.00
	40 DW	2060
	50 DW	2000

Printed on 4/23/2024 1:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..