

MT 612 - Tekniska specifikationer



Description

MT 612 är ett allrounddäck för användning både på väg och i terräng. Det kraftiga höljet gör det möjligt att transportera tunga laster vid höga hastigheter och de breda blocken ger utomordentlig dragkraft. Det extra breda slitbanemönstret ger utmärkta flytegenskaper på sand och lera.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Släpvagn

Industri: Universalfordon

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94036585
Ply Rating	22
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10

Load capacity (lbs)

mph / psi	125
50 LS	11680
50 LD	10470

Printed on 4/27/2024 8:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..