

## MT 612 - Ladda ned faktablad



### Description

MT 612 är ett allrounddäck för användning både på väg och i terräng. Det kraftiga höljet gör det möjligt att transportera tunga laster vid höga hastigheter och de breda blocken ger utomordentlig dragkraft. Det extra breda slitbanemönstret ger utmärkta flytegenskaper på sand och lera.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Släpvagn

Industri: Universalfordon

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.00 - 20	STANDARD	18	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	22	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	20	10		390	1265	594	3827	TT	E11-54R-0021125
16.0/70 - 20	STANDARD	16	13.00 T		405	1095	520	3327	TT	

Printed on 4/27/2024 10:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..