

MULTIMAX MP 513 - Tekniska specifikationer



Description

MULTIMAX MP 513 har designats av BKT för flerfunktionsfordon inom kommun/underhåll samt transporttillämpningar och är avsett för användning inom både lantbruk och industri. Det passar perfekt till universalfordon och gödslingsbilar. Tack vare det starka nylonhöljet med stålbalte har MULTIMAX MP 513 stor lastkapacitet även i hög hastighet och ger en bekväm körupplevelse. Tillsammans med enastående självrensande egenskaper lägger det grunden till längre livslängd och god dragförmåga.

UM

International Standard

Construction



RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil
Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	285/80 R 16 MPT
LI/SS	128 G

Dimensions International Standard

Section Width (mm)	304
Overall Diameter (mm)	866
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2617
Rim Rec	W 10
ECE	E11-54R-0020958

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0
90	840	985	1180	1360	1540	1800
65	905	1065	1270	1465	1660	1945
40	965	1135	1355	1560	1770	2070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..