

MULTIMAX MP 513 - Tekniska specifikationer



Description

MULTIMAX MP 513 har designats av BKT för flerfunktionsfordon inom kommun/underhåll samt transporttillämpningar och är avsett för användning inom både lantbruk och industri. Det passar perfekt till universalfordon och gödslingsbilar. Tack vare det starka nylonhöljet med stålbalte har MULTIMAX MP 513 stor lastkapacitet även i hög hastighet och ger en bekväm körupplevelse. Tillsammans med enastående självrensande egenskaper lägger det grunden till längre livslängd och god dragförmåga.

UM

International Standard

Construction



RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil
Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	365/70 R 18 MPT
LI/SS	133 G

Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	969
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2954
SRI (mm)	475
Rim Rec	11
Rim Alt	11 SDC ; 12 ; 12 SDC
ECE	E11-54R-0016138

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	3.75
90	1080	1280	1520	1760	2000	2060
65	1170	1380	1650	1910	2170	2240
40	1250	1470	1750	2020	2300	2370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 03:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..