

MULTIMAX MP 513 - Tekniska specifikationer



Description

MULTIMAX MP 513 har designats av BKT för flerfunktionsfordon inom kommun/underhåll samt transporttillämpningar och är avsett för användning inom både lantbruk och industri. Det passar perfekt till universalfordon och gödslingsbilar. Tack vare det starka nylonhöljet med stålbalte har MULTIMAX MP 513 stor lastkapacitet även i hög hastighet och ger en bekväm körupplevelse. Tillsammans med enastående självrensande egenskaper lägger det grunden till längre livslängd och god dragförmåga.

UM

International Standard

Construction



RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil
Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	425/55 R 17 MPT
LI/SS	142 A8/B

Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	900
Static Loaded Radius (mm)	399
Rolling Circumference (mm)	2705
Rim Rec	13
Rim Alt	13.00
ECE	E11-106R-006433

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
50	1035	1275	1515	1725	1965	2200	2440	2650
40	1035	1275	1515	1725	1965	2200	2440	2650
30	1110	1365	1620	1850	2105	2360	2530	2840
25	1150	1415	1680	1915	2180	2445	2625	2945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 11:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..