

MULTIMAX MP 513 - Tekniska specifikationer



Description

MULTIMAX MP 513 har designats av BKT för flerfunktionsfordon inom kommun/underhåll samt transporttillämpningar och är avsett för användning inom både lantbruk och industri. Det passar perfekt till universalfordon och gödslingsbilar. Tack vare det starka nylonhöljet med stålbalte har MULTIMAX MP 513 stor lastkapacitet även i hög hastighet och ger en bekväm körupplevelse. Tillsammans med enastående självrensande egenskaper lägger det grunden till längre livslängd och god dragförmåga.

UM

US Standard

Construction



RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil
Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

Dimensions US Standard

Usa code	94034703
Section Width (inch)	16.6
Overall Diameter (inch)	45.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	137
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0016141

Load capacity (lbs)

mph / psi	23	29	36	44	51	58
55	3390	3990	4740	5490	6220	6940
40	3690	4330	5150	5960	6750	7540
25	3910	4600	5460	6320	7150	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 11:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..