MULTIMAX MP 515 - Tekniska specifikationer

Description

MULTIMAX MP 515 är ett agroindustriradialdäck som är utformat för universalfordon och gödslingsbilar. Det är lämpligt för transporter och kommuntillämpningar. Däcket har en unik mönsterdesign som ger överlägsen åkkomfort på vägen och utmärkta självrensande egenskaper och fantastisk dragförmåga. Det starka däckhöljet av nylon med stålbälte och förstärkt skuldra gör däcket utomordentligt hållbart. MULTIMAX MP 515 är det perfekta däcket även vid höga hastigheter (90 km/h).

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	493
Rolling Circumference (mm)	3286
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC ; 11 SDC ; 11
ECE	E4-54R-0016565

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1340	1580	1820	2040	2240
65	1455	1715	1975	2215	2435
40	1545	1820	2095	2350	2580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 9:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..