MULTIMAX MP 515 - Tekniska specifikationer

Description

MULTIMAX MP 515 är ett agroindustriradialdäck som är utformat för universalfordon och gödslingsbilar. Det är lämpligt för transporter och kommuntillämpningar. Däcket har en unik mönsterdesign som ger överlägsen åkkomfort på vägen och utmärkta självrensande egenskaper och fantastisk dragförmåga. Det starka däckhöljet av nylon med stålbälte och förstärkt skuldra gör däcket utomordentligt hållbart. MULTIMAX MP 515 är det perfekta däcket även vid höga hastigheter (90 km/h).

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil

Version	STANDARD
Type	TL
Tyre Size	445/65 R 22.5 MPT
LI/SS	160 G

Dimensions International Standard

Section Width (mm)	444
Overall Diameter (mm)	1150
Static Loaded Radius (mm)	527
Rolling Circumference (mm)	3532
Rim Rec	13
Rim Alt	14
ECE	E11-54R-0017868

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5	4.0	4.5	6.0
90	1740	2060	2410	2750	3075	3390	3800	4500
65	1890	2235	2615	2985	3340	3675	4000	4885
40	2005	2365	2770	3165	3540	3900	4240	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 11:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..