MULTIMAX MP 515 - Ladda ned faktablad

Description

MULTIMAX MP 515 är ett agroindustriradialdäck som är utformat för universalfordon och gödslingsbilar. Det är lämpligt för transporter och kommuntillämpningar. Däcket har en unik mönsterdesign som ger överlägsen åkkomfort på vägen och utmärkta självrensande egenskaper och fantastisk dragförmåga. Det starka däckhöljet av nylon med stålbälte och förstärkt skuldra gör däcket utomordentligt hållbart. MULTIMAX MP 515 är det perfekta däcket även vid höga hastigheter (90 km/h).

UM

US Standard

Construction

RADIAL

Machinery

Lantbruk: Universalfordon • Gödslingsbil

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
405/70 R 20 MPT	STANDARD	94056545	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	16	42.4	19.4	129.4	TL	E4-54R-0016565
425/75 R 20 MPT	STANDARD	94055975	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	16.6	45.1	20.6	137.4	TL	E11-54R-0017872
445/65 R 22.5 MPT	STANDARD	94057207	160 G	13	14	17.5	45.3	20.7	139.1	TL	E11-54R-0017868

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 8:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..