

## MULTIMAX MP 527 - Tekniska specifikationer



### Description

MULTIMAX MP 527 är ett flerk Funktionsradialdäck designat för teleskoplastare och kompakthjullastare inom industriella lantbrukstillämpningar. Däcket är utformat med ett blockmönster som ger utmärkt dragförmåga även på hårdare underlag. Den starka sidoväggen ger enastående stabilitet i lyftläget. MULTIMAX MP 527 är tillverkat av en speciell gummiblandning med motståndskraft mot skärande underlag och punkteringar som ger längre livslängd.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Kompakthjullastare • Teleskoplastare  
Industri: Kompakthjullastare • Teleskoplastare

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 340/80 R 20 IND |
| LI/SS     | 144 A8/B        |

## Dimensions International Standard

|                            |                                  |
|----------------------------|----------------------------------|
| Section Width (mm)         | 343                              |
| Overall Diameter (mm)      | 1052                             |
| Static Loaded Radius (mm)  | 483                              |
| Rolling Circumference (mm) | 3176                             |
| SRI (mm)                   | 500                              |
| Rim Rec                    | 11                               |
| Rim Alt                    | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC |
| ECE                        | E11-106R-003957                  |

## Load capacity (Kg)

| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 1345 | 1600 | 1820 | 2075 | 2325 | 2495 | 2800 | -    | -    |
| 40         | 1345 | 1600 | 1820 | 2075 | 2325 | 2495 | 2800 | -    | -    |
| 30         | 1440 | 1710 | 1950 | 2220 | 2490 | 2670 | 3000 | -    | -    |
| 25         | 1495 | 1775 | 2025 | 2305 | 2585 | 2770 | 3110 | -    | -    |
| 10 Cyc.    | 1640 | 2020 | 2375 | 2730 | 3110 | 3385 | 3825 | 4035 | 4200 |
| Static     | 2515 | 3095 | 3640 | 4190 | 4770 | 5185 | 5865 | 6185 | 6440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..