

# MULTIMAX MP 529 - Tekniska specifikationer



## Description

MULTIMAX MP 529 är ett flerfunktionsradialdäck med stålbelte designat för teleskoplastare inom industriella tillämpningar. Mönsterdesignen har tagits fram speciellt för hårda underlag. Den starka sidoväggen och ett större avtryck ger enastående stabilitet i lyftläget. MULTIMAX MP 529 är tillverkat med ett starkt hölje och en speciell gummiblandning som gör det utomordentligt skär- och punkteringsbeständigt, med exceptionell hållbarhet och lång livslängd.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Industri: Teleskoplastare

|           |              |
|-----------|--------------|
| Version   | STEEL BELTED |
| Type      | TL           |
| Tyre Size | 340/80 R 18  |
| LI/SS     | 143 A8/B     |

## Dimensions International Standard

|                            |                    |
|----------------------------|--------------------|
| Section Width (mm)         | 343                |
| Overall Diameter (mm)      | 1001               |
| Static Loaded Radius (mm)  | 445                |
| Rolling Circumference (mm) | 3007               |
| SRI (mm)                   | 475                |
| Rim Rec                    | 11 ; 11 SDC ; W 11 |
| Rim Alt                    | W 10 ; 12 ; 12 SDC |
| ECE                        | E11-106R-002972    |

## Load capacity (Kg)

|            |      |      |      |      |      |      |      |      |      |
|------------|------|------|------|------|------|------|------|------|------|
| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4  |
| 50         | 1310 | 1555 | 1775 | 2020 | 2265 | 2430 | 2725 | -    | -    |
| 40         | 1310 | 1555 | 1775 | 2020 | 2265 | 2430 | 2725 | -    | -    |
| 30         | 1405 | 1665 | 1900 | 2165 | 2425 | 2600 | 2920 | -    | -    |
| 25         | 1455 | 1725 | 1970 | 2240 | 2515 | 2695 | 3025 | -    | -    |
| 10 Cyc.    | 1600 | 1965 | 2315 | 2660 | 3030 | 3295 | 3725 | 3930 | 4090 |
| Static     | 2450 | 3010 | 3545 | 4080 | 4640 | 5050 | 5710 | 6020 | 6270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..