

MULTIMAX MP 540 - Tekniska specifikationer



Description

MULTIMAX MP 540 har utvecklats av BKT för alla flerfunktionsfordon. Tack vare stålradiestommen har MULTIMAX MP 540 stor lastkapacitet både på vägar och i terrängen. Dessutom ger blockmönsterdesignen enastående stabilitet och hållbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Universalfordon

Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	275/80 R 20 (10.5 R 20)
LI/SS	134 K

Dimensions US Standard

Usa code	94071357
Overall Width (inch)	10.6
Overall Diameter (inch)	37.6
Static Loaded Radius (inch)	17.4
Rolling Circumference (inch)	114.7
Rim Rec	W9
Rim Alt	9
ECE	E11-54R-0020628

Load capacity (lbs)

mph / psi	75
68	4675

Printed on 5/6/2024 6:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..