

MULTIMAX MP 540 - Ladda ned faktablad



Description

MULTIMAX MP 540 har utvecklats av BKT för alla flerfunktionsfordon. Tack vare stålradiestommen har MULTIMAX MP 540 stor lastkapacitet både på vägar och i terrängen. Dessutom ger blockmönsterdesignen enastående stabilitet och hållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Universalfordon

Industri: Universalfordon

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
315/55 R 16	STANDARD	120 K / 124 F	W10L	11	305	751	354	2325	TL	E11-54R-0019558
335/80 R 18 (12.5 R 18)	STANDARD	132 K	11		340	985	446	3000	TL	E11-54R-0019559
275/80 R 20 (10.5 R 20)	STANDARD	134 K	W9	9	270	955	443	2913	TL	E11-54R-0020628
335/80 R 20	STANDARD	149 K	11	-	340	1044	492	3258	TL	E11-54R-0015909
365/80 R 20 (14.5 R 20)	STANDARD	152 K	11		365	1086	495	3308	TL	E11-54R-0020145
405/70 R 20 (16.0/70 R 20)	STANDARD	152 K	13	12; 13 SDC	402	1082	490	3295	TL	
405/70 R 24 (16.0/70 R 24)	STANDARD	152 J	13		402	1174	530	3586	TL	E11-54R-0020862

Printed on 5/6/2024 5:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..