

## MULTIMAX MT 518 - Tekniska specifikationer



### Description

MULTIMAX MT 518 är ett däck för militära lastbilar. Däcket är blockmönstrat och stålbeltat, har högt skydd mot punkteringar och utomordentlig stabilitet. MULTIMAX MT 518 tål dessutom höga hastigheter och har extra lång livslängd.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industri: Försvarslastbil

|           |                  |
|-----------|------------------|
| Version   | STANDARD         |
| Type      | TL               |
| Tyre Size | 36 X 12.5 R 16.5 |
| LI/SS     | 129 N            |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94039517        |
| Section Width (inch)         | 12.4            |
| Overall Diameter (inch)      | 35.5            |
| Static Loaded Radius (inch)  | 16.5            |
| Rolling Circumference (inch) | 108.6           |
| Rim Rec                      | 9.75            |
| ECE                          | E11-54R-0017917 |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 65   |
| 85        | 4080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 03/05/2025 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..