

## MULTIMAX SR 261 - Tekniska specifikationer



### Description

MULTIMAX SR 261 är ett radialdäck helt i stål med stålbälten i flera lager som är särskilt utformat för lågbyggd släpvagn, lantbrukssläpvagn och mobila hamnkranar i transporttillämpningar och hamnverksamhet.

Dess starka stomme och speciella mönstersammansättning säkerställer längre livslängd för däcken. Tack vare det lamellformade däckmönstret ger MULTIMAX SR 261 överlägsen dragförmåga i alla tillämpningar.

Dessutom maximerar den unika 5 RIB-mönsterdesignen markkontakten för ett jämnt slitage av däckmönstret.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industri: Släpvagn med låg plattform • Kranbil

Version	STANDARD
Type	TL
Tyre Size	285/70 R 19.5
LI/SS	150/148 J

## Dimensions US Standard

Usa code	94067688
Overall Width (inch)	11
Overall Diameter (inch)	35.6
Static Loaded Radius (inch)	16.2
Rolling Circumference (inch)	109.4
Rim Rec	8.25
Rim Alt	7.50 ; 9.00

## Load capacity (lbs)

mph / psi	130
62 Load Single	7400
62 Load Dual	6950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/11/2025 1:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..