

MULTIMAX SR 261 - Ladda ned faktablad



Description

MULTIMAX SR 261 är ett radialdäck helt i stål med stålbalten i flera lager som är särskilt utformat för lågbyggd släpvagn, lantbrukssläpvagn och mobila hamnkranar i transporttillämpningar och hamnverksamhet.

Dess starka stomme och speciella mönstersammansättning säkerställer längre livslängd för däcken. Tack vare det lamellformade däckmönstret ger MULTIMAX SR 261 överlägsen dragförmåga i alla tillämpningar.

Dessutom maximerar den unika 5 RIB-mönsterdesignen markkontakten för ett jämnt slitage av däckmönstret.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Släpvagn med låg plattform • Kranbil

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
215/75 R 17.5	STANDARD	94071067	135/133 J	6.00	6.75	8.3	30.5	14	93.3	TL
285/70 R 19.5	STANDARD	94067688	150/148 J	8.25	7.50 ; 9.00	11	35.6	16.2	109.4	TL

Printed on 4/27/2024 7:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..