

## PAC MASTER PLUS - Tekniska specifikationer



### Description

PAC MASTER PLUS är ett diagonaldäck för kompaktorer. Det har hög stabilitet och bredare kontaktyta. Däcket är tillverkat av en speciell gummiblandning som gör att det tål höga temperaturer. PAC MASTER PLUS är ett däck med en längre livscykel.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Kompaktfordon

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	225
Overall Diameter (mm)	790
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2385
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

## Load capacity (Kg)

km/h / bar	8.75
10	2900
15	2300

Printed on 4/28/2024 2:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..