

PAC MASTER - Tekniska specifikationer



Description

PAC MASTER är ett diagonaldäck för kompaktorer. Det har hög stabilitet och extra lång livslängd. Däcket är tillverkat av en extra värmetålig gummiblandning.

UM

US Standard

Construction



Machinery

Industri: Kompaktfordon

Version	STANDARD
Туре	TL
Tyre Size	10.5/80 - 16

Dimensions US Standard

Usa code	94053278
Ply Rating	14
Section Width (inch)	10.8
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	97.6
Rim Rec	8.0
ECE	E11-106R-004647

Load capacity (lbs)

mph / psi	87
5	6120
10	4960

Printed on 4/23/2024 1:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..