

PAC MASTER - Tekniska specifikationer



Description

PAC MASTER är ett diagonaldäck för kompaktorer. Det har hög stabilitet och extra lång livslängd. Däcket är tillverkat av en extra värmetålig gummiblandning.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Kompaktfordon

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 10.5/80 - 16 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94002467 |
| Ply Rating | 6 |
| Section Width (inch) | 10.8 |
| Overall Diameter (inch) | 31.9 |
| Static Loaded Radius (inch) | 15 |
| Rolling Circumference (inch) | 97.6 |
| Rim Rec | 8.0 |
| ECE | E11-106R-005274 |

Load capacity (lbs)

| mph / psi | 65 |
|-----------|------|
| 5 | 4080 |
| 10 | 3310 |

Printed on 4/23/2024 12:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..