

## PL 801 - Tekniska specifikationer



### Description

PL 801 är ett däck för höskörd med rotorvändare/strängvändare. Det passar även för gaffeltruckar som används för logistiktillämpningar. Det är mycket stabilt och extra tåligt mot skär- och skrapskador. PL 801 är ett däck med en längre livscykel.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Höskördemaskin • Roterande harv • Gaffeltruck  
Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	21 X 8 - 9 (200/75 - 9)

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	200
Overall Diameter (mm)	535
Rim Rec	6.00 E
Rim Alt	7.00 E

## Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	2755
25 STEER WHEEL	2120
10 OTHER VEHICLES	2755
25 OTHER VEHICLES	2120
STATIC SIDE LOADER	3200

Printed on 4/26/2024 12:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..