

PL 801 - Tekniska specifikationer



Description

PL 801 är ett däck för höskörd med rotorvändare/strängvändare. Det passar även för gaffeltruckar som används för logistiktillämpningar. Det är mycket stabilt och extra tåligt mot skär- och skrapskador. PL 801 är ett däck med en längre livscykel.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Höskördemaskin • Roterande harv • Gaffeltruck
Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

Dimensions International Standard

Ply Rating	12
Section Width (mm)	215
Overall Diameter (mm)	720
Rim Rec	7.0
Rim Alt	7.00 BD

Load capacity (Kg)

	km/h / bar	8.30
25 LOAD WHEEL		3445
25 STEER WHEEL		2650
10 OTHER VEHICLES		3445
25 OTHER VEHICLES		2650
STATIC SIDE LOADER		4000

Printed on 4/26/2024 11:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..