

PL 846 - Ladda ned faktablad



Description

PL 846 är avsett för jordbruksredskap som används för jordbearbetning. Det har utmärkt stabilitet och utomordentlig dragkraft, och är extra tåligt mot skär- och skrapskador. PL 846 är idealiskt att använda på steniga underlag.

UM

International Standard

Construction



Machinery

Lantbruk: Arbetsfordon

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
6.00 - 9	STANDARD	10	4.00 E		160	540	TT
6.00 - 9	STANDARD	12	4.00 E		160	540	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 3:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..