

PORT KING CLASSIC - Tekniska specifikationer



Description

PORT KING CLASSIC är senaste generationens hamndäck från BKT och har konstruerats särskilt för containerhanteringsutrustning. Däcket säkerställer maximal drifteffektivitet och enastående stabilitet i lyftläget. Tack vare det starka nylonhöljet imponerar PORT KING CLASSIC med extra hög lastkapacitet och minimerar risken för revor, hål och punkteringar till följd av stötar. Den nya, slitstarka gummiblandningen har tagits fram för att säkerställa längre livslängd och ge maximal valuta för pengarna.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Reachstacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94054480
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	195.1
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	50625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 6:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..