

PORTMAX PM 90 - Tekniska specifikationer



Description

PORTMAX PM 90 har utvecklats särskilt för reachstackers inom olika tillämpningar som industriell hantering och stålverk. Det är ett radialdäck helt i stål som ger fantastisk stabilitet och hållbarhet. Den speciella, antistatiska gummiblandningen ger hög motståndskraft mot värme och längre livslängd. PORTMAX PM 90 erbjuder lägre rullningsmotstånd för bättre bränsleekonomi.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Reachstacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

Dimensions US Standard

Usa code	94057184
Overall Width (inch)	19.1
Overall Diameter (inch)	72.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	221.4
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

Load capacity (lbs)

mph / psi	145
15	46700

Printed on 4/26/2024 7:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..