

## PORTMAX PT 93 - Tekniska specifikationer



### Description

PORTMAX PT 93 är ett däck för terminaltraktorer och släpvagnar och specialkonstruerat för tunga tillämpningar i terminalmiljöer som hamnar och logistikcenter. Den speciella antistatiska gummiblandningen säkerställer utmärkt slitstyrka och värmemotstånd i de mest krävande användningsmiljöer. PORTMAX PT 93 besitter utmärkta hanteringsegenskaper, ger enastående grepp och har extra lång hållbarhet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industri: Terminaltraktor • Släpvagn

Version	INDUSTRIAL
Type	TL
Tyre Size	280/75 R 22.5
LI/SS	168 A8

## Dimensions International Standard

Overall Width (mm)	282
Overall Diameter (mm)	998
Rim Rec	8.25
Rim Alt	9.00

## Load capacity (Kg)

km/h / bar	10.00
40	5600

Printed on 4/26/2024 6:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..