

PORTMAX PT 93 - Ladda ned faktablad



Description

PORTMAX PT 93 är ett däck för terminaltraktorer och släpvagnar och specialkonstruerat för tunga tillämpningar i terminalmiljöer som hamnar och logistikcenter. Den speciella antistatiska gummiblandningen säkerställer utmärkt slitstyrka och värmemotstånd i de mest krävande användningsmiljöer. PORTMAX PT 93 besitter utmärkta hanteringsegenskaper, ger enastående grepp och har extra lång hållbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Terminaltraktor • Släpvagn

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type
280/75 R 22.5	INDUSTRIAL	94053902	168 A8	8.25	9.00	11.1	39.3	TL
310/80 R 22.5	INDUSTRIAL	94057764	175 A8	9.00		12.1	42.1	TL
315/60 R 22.5	INDUSTRIAL	94067855	170 A8	9.75	9.00	12.1	38	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 3:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..