

POWER TRAX HD (FL) - Tekniska specifikationer



Description

POWER TRAX HD är ett förstklassigt däck som är specialdesignat för industriella gaffeltruckar. Den djupa slitbanan, den extra tjocka sidoväggen och det hårda höljet ger exceptionell hållbarhet och minimerar risken för punkteringar och oavsiktliga skador. Däcket har ett utmärkt skär-, flis- och slitmotstånd som är lämpligt för grov och hård betongyta. Det specialdesignade fälgskyddet garanterar skydd mot punkteringar och hjulskador i fälgområdet.

UM

US Standard

Construction

❖ BIAS

Machinery

Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	10.00L - 15 (36 X 11 - 15)

Dimensions US Standard

Usa code	94007653
Ply Rating	24
Section Width (inch)	11.2
Overall Diameter (inch)	36.1
Rim Rec	7.50 BD
Rim Alt	7.5

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	13755
15 STEER WHEEL	10580
5 OTHER VEHICLES	13755
15 OTHER VEHICLES	10580
STATIC SIDE LOADER	15985

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/4/2024 4:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..