

## POWER TRAX HD (FL) - Tekniska specifikationer



### Description

POWER TRAX HD är ett förstklassigt däck som är specialdesignat för industriella gaffeltruckar. Den djupa slitbanan, den extra tjocka sidoväggen och det hårda höljet ger exceptionell hållbarhet och minimerar risken för punkteringar och oavsiktliga skador. Däcket har ett utmärkt skär-, flis- och slitmotstånd som är lämpligt för grov och hård betongyta. Det specialdesignade fälgskyddet garanterar skydd mot punkteringar och hjulskador i fälgområdet.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Industri: Gaffeltruck

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 9.00 - 20 |

## Dimensions US Standard

|                         |                 |
|-------------------------|-----------------|
| Usa code                | 94060108        |
| Ply Rating              | 16              |
| Section Width (inch)    | 10.6            |
| Overall Diameter (inch) | 41.3            |
| Rim Rec                 | 7.0             |
| Rim Alt                 | 7.5             |
| ECE                     | E11-106R-005554 |

## Load capacity (lbs)

| mph / psi          | 145   |
|--------------------|-------|
| 15 LOAD WHEEL      | 13615 |
| 15 STEER WHEEL     | 10470 |
| 5 OTHER VEHICLES   | 13615 |
| 15 OTHER VEHICLES  | 10470 |
| STATIC SIDE LOADER | 15815 |

Printed on 4/26/2024 8:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..