



## POWER TRAX HD (FL) - Ladda ned faktablad



### Description

POWER TRAX HD är ett förstklassigt däck som är specialdesignat för industriella gaffeltruckar. Den djupa slitbanan, den extra tjocka sidoväggen och det hårda höljet ger exceptionell hållbarhet och minimerar risken för punkteringar och oavsiktliga skador. Däcket har ett utmärkt skär-, flis- och slitmotstånd som är lämpligt för grov och hård betongyta. Det specialdesignade fälgskyddet garanterar skydd mot punkteringar och hjulskador i fälgområdet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Gaffeltruck

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>18 X 7 - 8</b> (180/70 - 8)	STANDARD	94007691		16	4.33 R	5.00 F	6.8	18.5	0	0	TT	
<b>5.00 - 8</b>	STANDARD	94007790		10	3.00 D	3.25 I	5.7	18.9	0	0	TT	
<b>6.00 - 9</b>	STANDARD	94007806		10	4.00 E		6.5	21.4	0	0	TT	
<b>23 X 9 - 10</b> (225/75 - 10)	STANDARD	94007714		20	6.50 F		9.3	23.2	0	0	TT	E11-106R-005849
<b>23 X 9 - 10</b> (225/75 - 10)	STANDARD	94007707		18	6.50 F		9.3	23.2	0	0	TT	
<b>6.50 - 10</b>	STANDARD	94007813		10	5.00 F	5.50 F	7.6	23.4	10.9	69.8	TT	
<b>6.50 - 10</b>	STANDARD	94032297		12	5.00 F	5.50 F	7.6	23.4	10.9	69.8	TT	
<b>6.50 - 10</b>	STANDARD	94032242		14	5.00 F	5.50 F	7.6	23.4	10.9	69.8	TT	
<b>27 X 10 - 12</b> (250/75 - 12)	IMPLEMENT	94058051	148 A8	20	8.00 G		10	27.2	0	0	TT	E11-106R-003409
<b>27 X 10 - 12</b> (250/75 - 12)	IMPLEMENT	94060634	142 A8	16	8.00 G		10	27.2	0	0	TT	E11-106R-003399
<b>27 X 10 - 12</b> (250/75 - 12)	STANDARD	94007752		16	8.00 G		10	27.2	0	0	TT	
<b>27 X 10 - 12</b> (250/75 - 12)	STANDARD	94007769		20	8.00 G		10	27.2	0	0	TT	
<b>7.00 - 12</b>	STANDARD	94007820		14	5.00 S		8.1	26.6	0	0	TT	
<b>7.00 - 12</b>	STANDARD	94032228		16	5.00 S		8.1	26.6	0	0	TT	
<b>10.00L - 15</b> (36 X 11 - 15)	STANDARD	94007646		16	7.50 BD	7.5	11.2	36.1	0	0	TT	
<b>10.00L - 15</b> (36 X 11 - 15)	STANDARD	94007653		24	7.50 BD	7.5	11.2	36.1	0	0	TT	
<b>250 - 15</b> (250/70 - 15)	STANDARD	94007738		18	7.50	7.0	9.4	29.3	0	0	TT	
<b>250 - 15</b> (250/70 - 15)	STANDARD	94007745		20	7.50	7.0	9.4	29.3	0	0	TT	
<b>250 - 15</b> (250/70 - 15)	STANDARD	94007721		16	7.50	7.0	9.4	29.3	0	0	TT	
<b>28 X 12.5 - 15</b>	IMPLEMENT	94056002	149 A8	24	9.75 BD		12	27.8	0	0	TT	E11-106R-003423
<b>28 X 12.5 - 15</b>	STANDARD	94048649		24	9.75 BD		12	27.8	0	0	TT	
<b>300 - 15</b> (315/70 - 15)	STANDARD	94007776		20	8.00		11.8	33.3	0	0	TT	
<b>8.15 - 15</b> (28 X 9 - 15)	STANDARD	94007844		14	7.00	7 BD	8.9	28	0	0	TT	
<b>8.25 - 15</b>	STANDARD	94007875		14	6.50	7.0	9.8	33.3	0	0	TT	
<b>8.25 - 15</b>	STANDARD	94026012		16	6.50	7.0	9.8	33.3	0	0	TT	
<b>10.00 - 20</b>	IMPLEMENT	94058068	160 A8	16	7.5	8.0	11.2	42.5	0	0	TT	E11-106R-003664
<b>10.00 - 20</b>	STANDARD	94007622		16	7.5	8.0	11.2	42.5	0	0	TT	
<b>10.00 - 20</b>	STANDARD	94007639		18	7.5	8.0	11.2	42.5	0	0	TT	E11-106R-005560
<b>9.00 - 20</b>	STANDARD	94060108		16	7.0	7.5	10.6	41.3	0	0	TT	E11-106R-005554

Printed on 4/26/2024 8:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part,

