

POWER TRAX HD SMOOTH - Tekniska specifikationer



Description

POWER TRAX HD SMOOTH är ett diagonaldäck avsett för användning i hamnar och gruvor. Det särskilda sidoväggsskyddet i kombination med de solida trådarna motverkar skär- och punkteringsskador som är vanliga i dessa krävande miljöer. Power Trax HD Smooth är en idealisk partner vid hanteringen av tunga laster.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Containerhanterare • Gaffeltruck
OTR: Underjordiskt gruvfordon

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94062997
Ply Rating	28
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20920
15 STEER WHEEL	16095
5 OTHER VEHICLES	20920
15 OTHER VEHICLES	16095
STATIC SIDE LOADER	24305

Printed on 2/22/2024 9:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..