

POWER TRAX HD - Tekniska specifikationer



Description

Premiumdäcket POWER TRAX HD är speciellt utformat för hamn- och underjordisk gruvutrustning. Dess djupa slitbana, den extra tjocka sidoväggen och det hårda höljet ger exceptionell hållbarhet och minimerar risken för punkteringar och oavsiktliga skador. Däcket har ett utmärkt skär- och flismotstånd som är särskilt lämpligt för grova och hårda ytor. Det specialdesignade fälgskyddet garanterar skydd mot punkteringar och hjulskada i fälgområdet.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Containerhanterare

OTR: Underjordiskt gruvfordon

Version	IMPLEMENT
Type	TT
Tyre Size	12.00 - 20
LI/SS	173 A8

Dimensions US Standard

Usa code	94055951
Ply Rating	28
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-003348
Tread Depth	43

Load capacity (lbs)

mph / psi	145
25	14300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..