

POWER TRAX - Tekniska specifikationer



Description

POWER TRAX är ett premiumdäck speciellt designat för tunga applikationer på hamntrailer, tomcontainerhanterare eller ECH och underjordiska gruvmaskiner. Dess djupa slitbana och tjocka sidovägg ger exceptionell hållbarhet, vilket minimerar risken för punkteringar och oavsiktlig skada. POWER TRAX är det idealiska däck för hårda och tuffa arbetsmoment, tack vare den unika slitbaneblandningen som ger utmärkt motståndskraft mot skär- och skrapskador.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Tomcontainerhanterare
OTR: Underjordiskt gruvfordon

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20
LI/SS	176 A5

Dimensions US Standard

Usa code	94067701
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.5
Rim Alt	9.0

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20350
15 STEER WHEEL	15650
5 OTHER VEHICLES	20350
15 OTHER VEHICLES	15650
STATIC SIDE LOADER	23630

Printed on 4/27/2024 9:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..