

## PUDDLE SPECIAL (A) - Tekniska specifikationer



### Description

PUDDLE SPECIAL är ett R-2-jordbruksdäck avsett för användning på risfält. Det extra djupa slitbanemönstret ger, tillsammans med det speciella blockmönstret, bästa möjliga grepp och utmärkt dragkraft även på blöt och mjuk jord. Den breda mittribban gör däckets bättre lämpat för användning på vägar och ger utomordentlig prestanda. PUDDLE SPECIAL har dessutom överlägsna självrensande egenskaper och utmärkt pålitlighet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	11 - 32
LI/SS	111 A2

## Dimensions US Standard

Usa code	94049011
Ply Rating	6
Section Width (inch)	12
Overall Diameter (inch)	57.7
Static Loaded Radius (inch)	27.6
Rolling Circumference (inch)	172.6
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

## Load capacity (lbs)

mph / psi	23
5	2380

Printed on 12/5/2023 10:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..