

PUDDLE SPECIAL (B) - Tekniska specifikationer



Description

PUDDLE SPECIAL är ett R-2-jordbruksdäck avsett för användning på risfält. Det extra djupa slitbanemönstret ger, tillsammans med det speciella blockmönstret, bästa möjliga grepp och utmärkt dragkraft även på blöt och mjuk jord. Den breda mittribban gör däcket bättre lämpat för användning på vägar och ger utomordentlig prestanda. PUDDLE SPECIAL har dessutom överlägsna självrensande egenskaper och utmärkt pålitlighet.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Besprutningsbil

Version	STANDARD
Type	TT
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	127
Overall Diameter (mm)	940
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-005236

Load capacity (Kg)

km/h / bar	3.00
10	600

Printed on 4/16/2024 11:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..