

## RIB 324 - Tekniska specifikationer



### Description

RIB 324 har ett specialformat däckmönster och en stor kontaktyta för bästa möjliga stabilitet och flyt på löst underlag och i sandig terräng. Det starka däckhöljet i nylon och specialgummiblandningen har en grym motståndskraft mot punkteringar och slitage och klarar även enkelt av högre lastkapacitet.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon

Industri: Släpvagn

Version	STANDARD
Type	TL
Tyre Size	66 X 44.00 - 25

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Section Width (mm)</b>	1110
<b>Overall Diameter (mm)</b>	1700
<b>Rim Rec</b>	36.0 TH

## Load capacity (Kg)

km/h / bar	3.50
50	7300

Printed on 4/19/2024 4:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..