

## RIB 774 (A) - Tekniska specifikationer



### Description

RIB 774 (A) är ett implementdäck med låg profil, hög lastkapacitet och lägsta möjliga jordpackning. Det passar perfekt för moderna jordbruk och kan användas både på väg och i terräng.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	10.5/65 - 16
LI/SS FREE ROLLING	130 A8

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	265
<b>Overall Diameter (mm)</b>	745
<b>Static Loaded Radius (mm)</b>	339
<b>Rolling Circumference (mm)</b>	2183
<b>Rim Rec</b>	W 9
<b>Rim Alt</b>	W 8 L
<b>ECE</b>	E11-106R-004312

## Load capacity (Kg)

	km/h / bar	5.30
	10 FR	2660
	25 FR	2260
	30 FR	2130
	40 FR	1900

Printed on 4/18/2024 9:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..