

RIB 774 (A) - Tekniska specifikationer



Description

RIB 774 (A) är ett implementdäck med låg profil, hög lastkapacitet och lägsta möjliga jordpackning. Det passar perfekt för moderna jordbruk och kan användas både på väg och i terräng.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-003608

Load capacity (Kg)

	km/h / bar	7.00
	10 FR	1610
	25 FR	1370
	30 FR	1290
	40 FR	1150

Printed on 4/20/2024 5:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..