RIB 774 (B) - Tekniska specifikationer

Description

RIB 774 (B) är ett redskapsdäck med låga sektioner. Det är ett idealiskt däck för det moderna lantbruket och lämpar sig för körning både på väg och i terräng med arbetsfordon och släpvagnar. Det erbjuder imponerande lastkapacitet och har lång livslängd. Det finns även en “HD”-version för tung tjänst.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn
Industri: Släpvagn

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004309

Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 11:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..