

## RIB 774 (C) - Tekniska specifikationer



### Description

RIB 774 (C) är ett redskapsdäck med låga sektioner och smal bredd. Det passar utmärkt till höskördning och transporttillämpningar med balpress och släpvagn, både på vägen och åkern. Det erbjuder imponerande lastkapacitet och har lång livslängd.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Släpvagn

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 225/75 - 17.5 |
| LI/SS FREE ROLLING | 134 A8        |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94011025        |
| Ply Rating                   | 12              |
| Section Width (inch)         | 8.7             |
| Overall Diameter (inch)      | 30.5            |
| Static Loaded Radius (inch)  | 14.2            |
| Rolling Circumference (inch) | 90.9            |
| Rim Rec                      | 6.75            |
| ECE                          | E11-106R-004657 |

## Load capacity (lbs)

| mph / psi | 100  |
|-----------|------|
| 5 FR      | 6550 |
| 15 FR     | 5570 |
| 20 FR     | 5240 |
| 25 FR     | 4670 |

Printed on 4/28/2024 2:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..