

RIB 900 - Tekniska specifikationer



Description

RIB 900 lämpar sig för transporter, jordbearbetning och höskördning med släpvagnar, arbetsfordon och balpressar. Det erbjuder fantastisk lastkapacitet och har lång livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Arbetsfordon •
Släpvagn

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94026357
Ply Rating	10
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00

Load capacity (lbs)

mph / psi	36
5 FR	6910
15 FR	5870
20 FR	5530
25 FR	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..