

RIB F3 - Tekniska specifikationer



Description

RIB F3 är ett fältorienterat däck konstruerat för tvåhjulsdreven traktorer som används till jordbearbetnings- och transportarbeten. Vissa storlekar lämpar sig för transportarbeten med släpvagn. RIB F3-däcket är en idealisk partner i alla former av verksamhet som kräver god hanteringsförmåga. Det är designat med en hård gummiblandning som ger fantastisk hållbarhet och motståndskraft mot stubb.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Tvåhjulsdreven traktor • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions US Standard

Usa code	94027781
Ply Rating	12
Section Width (inch)	9.6
Overall Diameter (inch)	34.6
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101.3
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004592
TRA Code	F3

Load capacity (lbs)

mph / psi	68
20	3090
25	2470

Printed on 4/20/2024 7:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..