RIB IMPLEMENT (B) - Tekniska specifikationer

Description

RIB IMPLEMENT (B) är särskilt konstruerat för jordbrukstillämpningar. Detta idealiska däck för det moderna jordbruket är tillverkat av en stubbtålig gummiblandning med utmärkt punkteringsskydd. RIB IMPLEMENT (B) är ett däck med fem mönsterribbor och starkt däckhölje för längre livslängd. Det är det rätta valet för alla användningsförhållanden som kräver hög lastkapacitet och lågt rullmotstånd.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions International Standard

Ply Rating	20
Section Width (mm)	425
Overall Diameter (mm)	1200
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (Kg)

km/h / bar	4.0
40 FR	4250
50 FR	3750
40 DW	3000
50 DW	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 6:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..