

## RIB TRAILER - Tekniska specifikationer



### Description

RIB TRAILER är ett diagonaldäck specialdesignat för körning på väg och offroad med arbetsfordon, framför allt halmskärare.

Konstruktionen med fyra mönsterringor optimerar lastfördelningen och det starka höljet ger motståndskraft mot stubb. RIB TRAILER har designats med en speciell gummiblandning som ger däckets extra lång livslängd tack vare den höga slitstyrkan.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

## Dimensions US Standard

Usa code	94070220
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	28.9
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F

## Load capacity (lbs)

mph / psi	68
25	1360

Printed on 4/23/2024 5:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..