

## RIDEMAX FL 615 - Ladda ned faktablad



### Description

RIDEMAX FL 615 är ett flotationsradialdäck som lämpar sig för icke-drivna hjul på släpvagnar, tankbilar och spridare. Stålbältestrukturen ger hög motståndskraft mot punktering med ökad hållbarhet och hög lastkapacitet. RIDEMAX FL 615 ger lågt rullningsmotstånd på vägen med utmärkta självrensande egenskaper på åkern. Den rundade däcksuldran och ett brett avtryck skyddar marken.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Spridare • Tankbil • Släpvagn

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
800/65 R 32	STEEL BELTED	94070176	185 D	185 D	185 D	DW 27 B		32.7	73	32.8	221.4	TL	E11-106R-007528

Printed on 4/27/2024 8:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..